

### Techna Clip Compatibility Chart

<i>Make</i>	<i>Gun Model</i>	<i>Size</i>	<i>Right Side</i>	<i>Left Side</i>	<i>Ambi</i>	<i>Item</i>
<b>Beretta</b>	Nano	Sub-Compact	X			NABR
<b>Diamondback</b>	DB9/DB380	Sub-Compact	X			DBBR
<b>Glock</b>	17, 19, 22, 23, 24, 25, 26, 27, 28, 30S, 31, 32, 33, 34, 35, 36	Full Size/Compact/Sub Com (Gen 1-4)			X	GLOCKBRL
<b>Glock</b>	G42 .380	Sub-Compact			X	G42BRL
<b>Glock</b>	G43 9mm	Sub-Compact			X	G43BRL
<b>Kahr</b>	9mm .40	Full Size/Compact/Sub Com	X			KHRBR
<b>Kimber</b>	Micro 9 9mm	Sub-Compact	X			MIC9BR
<b>Kel-Tec</b>	P3AT/P32	Sub-Compact	X			P3BR
<b>Sig Sauer</b>	P238 .380	Sub-Compact	X			P238BR
<b>Sig Sauer</b>	P320 9mm .357 .40 .45	Full Size/Compact/Carry/Sub Com			X	P320BA
<b>Sig Sauer</b>	P365 9mm	Sub-Compact			X	P365BA
<b>Sig Sauer</b>	P938 9mm	Sub-Compact	X			P938BR
<b>Smith &amp; Wesson</b>	Bodyguard .380	Sub-Compact	X			BDGBR
<b>Smith &amp; Wesson</b>	M&P 9mm .40 .45	Full Size/Compact/Sub Com			X	MPBA
<b>Smith &amp; Wesson</b>	M&P Shield 9mm .40	Compact (Gen 1 & 2)	X			SHBR
<b>Smith &amp; Wesson</b>	M&P Shield .45	Compact			X	SHBA
<b>Smith &amp; Wesson</b>	Small J-Frames made after 1998	Small J-Frames	X			JFRBR
<b>Smith &amp; Wesson</b>	SDVE 9mm .40	Full Size			X	SDBA
<b>Springfield Armory</b>	XD 9mm .40 .45	Full Size/Compact/Sub Com			X	XDBA
<b>Springfield Armory</b>	XD(M) and MOD.2 Models	Full Size/Compact/Sub Com	X			XDMBR
<b>Springfield Armory</b>	XD-S/XD-S MOD 2. Models	Compact			X	XDSBA
<b>Ruger</b>	LC9/LC	Sub-Compact	X			LC9BR
<b>Ruger</b>	LC9/LC	Sub-Compact		X		LC9BL
<b>Ruger</b>	LC9S/EC9S	Sub-Compact	X			LC9SBR
<b>Ruger</b>	LCP	Sub-Compact	X			LCPBR
<b>Ruger</b>	LCP	Sub-Compact		X		LCPBL
<b>Ruger</b>	LCP II	Sub-Compact	X			LCPIIBR
<b>Ruger</b>	SR 9mm .40	Full Size & Compact			X	SR9BA
<b>Taurus</b>	G2 Millennium/Slim Series	Compact			X	G2BA
<b>1911 Full Size</b>	Full Size Colt models, the Government, Commander and Clones built after the Colt 1911 frame. Grip screw placing is 3-1/16" apart	Full Size	X			COMBR
<b>1911 Compact</b>	Compact Colt models, the Defender, Officer and Clones built after the Colt frame. Grip screw placing is 2-11/16" apart	Compact	X			DEFBR